

TECHNICAL DATA SHEET v3.0 APRIL 2025

# **GUARANTAPE EXTREME MARATHON**

## **Adhesive Level 7**

### **PRODUCT OVERVIEW**

Marathon tape is our pure acrylic tape available in grey with a Red Filmic release liner. This pure acrylic adhesive system provides excellent UV and temperature resistance making it ideal for indoor and outdoor POS applications. It performs superbly when bonding glass, PVC, polycarbonates, stainless steel, aluminium and a wide variety of plastics.

### **SUITABLE FOR EXTERIOR USE**

### **SIZES AVAILABLE**

Flush: 12mm, 19mm, 24mm  
Roll Lengths: 50m individual rolls

### **BASE MATERIAL, LINER AND TAPE THICKNESS**

#### **PRODUCT CONSTRUCTION**

Liner: Red filmic  
Adhesive: Grey 1.5mm thickness, pure Acrylic  
Foam density: 760 kg/m<sup>3</sup>

### **STORAGE, APPLICATION AND SERVICE TEMPERATURE**

#### **PERFORMANCE PROPERTIES**

180° Peel Strength (N/cm)	63.7	ASTM D-3330
Shear Strength (N/6.54cm <sup>2</sup> )	491	ASTM D-1002
Tensile Strength (N/6.54cm <sup>2</sup> )	496	ASTM D-897
Temperature Resistance	Short Term	230°C
	Long Term	150°C

Shelf life: Recommended 12 months from supply. Store in dry and cool conditions.

### **TYPICAL APPLICATIONS**

Bonding for metal panels, sign work, product assembly.

The above information is given in good faith and for guidance only. All data is based on average values. The purchaser shall be responsible for determining the suitability for the actual use.

Contact your UK distributor for further information:

PRESCO UK LTD. PRY FARM, THE PRY, SWINDON SN5 4JP T: 01793 716300 E: [SALES@PRESCO.UK](mailto:SALES@PRESCO.UK)

[WWW.PRESCO.UK](http://WWW.PRESCO.UK)