

TECHNICAL DATA SHEET v3.0 APRIL 2025

GUARANTAPE PREMIUM MASKING TAPE

PRODUCT OVERVIEW

White crepe masking tape for studio work and many other specialist print & craft uses. Remove within 24hrs after use for a perfect finish.

NOT SUITABLE FOR EXTERIOR USE

SIZES AVAILABLE

Flush: 25mm, 50mm

Roll Lengths: 50m individual rolls

BASE MATERIAL, LINER AND TAPE THICKNESS

PRODUCT CONSTRUCTION

Backing: 59 g/m natural cream saturated crepe paper

Adhesive: natural rubber and resins solvent based

Total thickness: 0.120 mm

STORAGE, APPLICATION AND SERVICE TEMPERATURE

PERFORMANCE PROPERTIES

Adhesion to steel 4.25 N/25mm

Tensile strength MD 80 N/25mm

Elongation at break 8.5 %

Temperature resistance 60 °C (30 min)

Shelf life: Recommended 12 months from supply. Tape must be applied at room temperature for best results, and we do not recommend using this on high value or irreplaceable artwork and prints.

TYPICAL APPLICATIONS

Precision Painting - Delivers crisp, clean paint lines with excellent edge definition—ideal for decorators, automotive sprayers, and industrial coating.

General Purpose Masking - Great for everyday masking needs during sanding, spraying, or light-duty protection.

Bundling & Holding - Temporarily secures cables, components, or materials during assembly or transit.

Labeling & Marking - Easy to write on and remove, making it handy for temporary signage or jobsite instructions.

DIY & Craft Projects - Loved by hobbyists for its flexibility, clean removal, and no-nonsense reliability.

Construction & Renovation Sites - Used to mask windows, skirting boards, or fixtures—sticks well, removes cleanly, no drama.

The above information is given in good faith and for guidance only. All data is based on average values. The purchaser shall be responsible for determining the suitability for the actual use.

Contact your UK distributor for further information:

PRESCO UK LTD. PRY FARM, THE PRY, SWINDON SN5 4JP T: 01793 716300 E: SALES@PRESCO.UK

WWW.PRESCO.UK